

产品一览表 / PRODUCT LIST

◆小型铝电解电容器 / MINIATURE ALUMINUM ELECTROLYTIC CAPACITORS

	系列名称 SERIES	页码 PAGE	特 长 FEATURES	通用	小型薄型	高纹波电流	过电压对策规格设定品	长寿命	对RoHS	额定电压 RATED VOLTAGE (V.DC)	静电容量 RATED CAPACITANCE (μF)	工作温度范围 CATEGORY TEMPERATURE RANGE (°C)
				品	品	品	品	品	品			
开关电源用 FOR SWITCHING POWER SUPPLY	NEW BXW		105°C 10000小时、超小型化品 10000 HOURS ULTRA MINIATURIZED	●	●			●	●	400~450	15~220	-25~+105
	UPGRADE TXW		105°C 7000~10000小时、小型化品 7000~10000 HOURS, MINIATURIZED		●				●	35~100 160~450	12~1800	-40~+105 -25~+105
	CXW		105°C 5000小时、超小型化品 5000 HOURS, ULTRA MINIATURIZED		●				●	400~450	33~220	-25~+105
	QXW		105°C 超小型化品 ULTRA MINIATURIZED		●				●	400~450	27~220	-25~+105
	KXW		105°C 小型化品 MINIATURIZED		●				●	200~450	18~560	-25~+105
	SXW		过电压对策规格设定品 OVER-VOLTAGE VENTING SPECIFICATION				●		●	200,400	4.7~330	-25~+105
	SAW		小型化过电压对策规格设定品 MINIATURIZED, OVER-VOLTAGE VENTING SPECIFICATION		●		●		●	400	18~120	-25~+105

◆大型铝电解电容器 / LARGE CAN TYPE ALUMINUM ELECTROLYTIC CAPACITORS

基板自立型 SNAP-IN TYPE	MXH		105°C 超小型化品 ULTRA MINIATURIZED	●	●	●			●	400~450	100~820	-25~+105
	MXG		105°C 小型化品 MINIATURIZED	●	●	●			●	50~100 160~500	680~15000 39~2700	-40~+105 -25~+105
	MXC		105°C 标准品 STANDARD	●					●	10~100 160~450	560~68000 47~2700	-40~+105 -25~+105
	VXS		105°C 5000小时 充电规格品 5000 HOURS, CHARGE-DISCHARGE SPECIFIED TYPE					●	●	315~450	82~1000	-25~+105
	VXH		105°C 5000小时、小型化品 5000 HOURS, MINIATURIZED		●	●			●	200~450	100~2200	-25~+105
	UPGRADE VXG		105°C 5000小时品 5000 HOURS		●	●			●	10~100 200~500	560~56000 47~2200	-40~+105 -25~+105
	VXR		105°C 7000小时品 7000 HOURS			●			●	160~450	39~2200	-25~+105
	KXF		105°C 高20mm小型化品 20mm HEIGHT, MINIATURIZED	●	●				●	10~100 160~450	330~10000 39~820	-40~+105 -25~+105
	SXG		小型化过电压对策规格设定品 MINIATURIZED, OVER-VOLTAGE VENTING SPECIFICATION		●		●		●	200, 400, 450	39~1200	-25~+105
	SXC		过电压对策规格设定品 OVER-VOLTAGE VENTING SPECIFICATION				●		●	200, 400	22~1500	-25~+105
	USH		85°C 超小型化品 ULTRA MINIATURIZED	●	●				●	400~450	120~1000	-25~+85
	USG		85°C 小型化品 MINIATURIZED	●	●	●			●	160~250 400~450	220~3300 68~820	-40~+85 -25~+85
	USC		85°C 标准品 STANDARD	●					●	10~250 315~450	180~82000 56~1000	-40~+85 -25~+85
接头端子型 LUG TERMINAL TYPE	MXY		105°C 小型横置品 MINIATURIZED HORIZONTAL MOUNT		●				●	160~400	68~1500	-25~+105
螺栓端子型 SCREW TERMINAL TYPE	LSQ		85°C 3000小时品 3000 HOURS	●					●	10~100 160~450	2200~680000 270~33000	-40~+85 -25~+85
	LSU		85°C 5000小时品 5000 HOURS	●		●		●	●	350~500	1200~18000	-25~+85
	LSW		105°C 3000小时品 3000 HOURS	●					●	10~100 160~400	2200~680000 220~22000	-40~+105 -25~+105
	LSG		105°C 5000小时品 5000 HOURS	●		●		●	●	350~450	1000~18000	-25~+105

◆闪光灯用铝电解电容器 / PHOTO FLASH ALUMINUM ELECTROLYTIC CAPACITORS

系列名称 SERIES	页码 PAGE	特 长 FEATURES	对RoHS	额定电压 RATED VOLTAGE (V.DC)	静电容量 RATED CAPACITANCE (μF)	工作温度范围 CATEGORY TEMPERATURE RANGE (°C)
FK		接头端子标准品 STANDARD LUG TERMINAL	●	330	150~1500	-20~+55
				360	150~1300	
FKX		接头端子小型化品 MINIATURIZED LUG TERMINAL	●	330	150~1500	-20~+55
				360		
SF		接头端子高压品 HIGH VOLTAGE LUG TERMINAL	●	450	150~1000	-20~+55
FW		引线端子品 LEAD WIRE TERMINAL	●	330	10~300	-20~+60
CDF		接头端子闪光灯用 FOR FLASH LAMPS	●	360	60~400	-25~+70
				450	40~300	

◎注 意 CAUTION

以上的闪光灯用铝电解电容器只用于照相摄影用闪光灯(电子闪光灯), 不能用作其它用途。

These Rubycon Photo Flash Capacitors are designed, manufactured and intended solely for use in photo flash and other photographic equipment.

They are not intended for use in medical equipment.

Rubycon Corporation, Rubycon America, Inc., and Shin-Ei Capacitor Foil Company, Ltd. expressly disclaim any warranties or representations as to the suitability or fitness of these capacitors for use in medical equipment.