

◆ Please fill out the format with requests and send to us.

Date		Target date	
Name			
Company name		Section	
Telephone number		Fax number	
E-mail			

Item	Example	Requirements
Set	TV, PC, etc	
Application	Smoothing, Filtering, By-pass, Coupling, etc	
Production	Quantity, Prototype plan, Production plan	
Environment friendly	RoHS, etc	
Target price	Prototype price, Production price	
Type	Aluminum electrolytic capacitors Conductive polymer aluminum capacitors Film capacitors Polymer Multi-Layer capacitors	
Style	SMD, Radial lead, Snap-in, Screw terminal	
Rated voltage	50V.DC, 250V.AC, 800Vp-p	
Rated capacitance	100 $\mu$ F, 100pF	
Capacitance tolerance	$\pm 20\%$ (M), $\pm 10\%$ (K), $\pm 5\%$ (J), $\pm 3\%$ (H),	
Dimensions	Lead pitch Aluminum electrolytic capacitors ( $\phi$ DxL) Conductive polymer aluminum capacitors (LxWxH) Film capacitors (AxBxC)	
Temperature range	-40 $^{\circ}$ C~+105 $^{\circ}$ C	
Ripple current	Current, Frequency	
Operating condition	Operating time per day, Temperatures	
Life time	Guaranteed life, Expected life	
Soldering Conditions	Dip, Flow, Reflow Soldering temperature, Seaking time, times Peak temperature conditions, Preheating	
Other quality conditions	Impedance, Leakage current	
Other assembly conditions	Curing oven (temperature time), Adhesives	
Other conditions	Other specific requirements.	