

**DSA SERIES**

Load Life: 60°C 2000hours

◆ **FEATURES**

- Low Resistance
- RoHS compliance




◆ **SPECIFICATIONS**

Items	Characteristics	
Category Temperature Range	-25~+60°C	
Rated Voltage Range	2.5V.DC	
Capacitance Tolerance	±20%(20°C)	
Characteristics at High and low Temperatures	Capacitance Change	$ \Delta C/C(+20^\circ\text{C})  \leq 30\%$
	DC Internal Resistance	Max, 6 times of value at +20°C (at -25°C)
Endurance	After 2000 hours with rated voltage at 60°C, the capacitors shall meet the following requirements.	
	Capacitance Change	$ \Delta C/C(\text{initial})  \leq 30\%$
	DC Internal Resistance	Max, 3 times of the specification
Storage at High Temperature	After 2000 hours without load at 60°C, the capacitors shall meet the same requirements specified for endurance.	

◆ **PART NUMBER**



◆ **DIMENSIONS**



◆ **STANDARD SIZE**

Rated Voltage (V.DC)	Rated Capacitance (F)	DC Internal Resistance (mΩ)	φ D×L (mm)	Part No.
2.5	850	4	36×135	2.5DSA850□36×135
	1900	2	51×135	2.5DSA1900□51×135

□: Tolerance(M: ±20)