

MPC/MPCA SERIES
◆FEATURES•APPLICATION

- Low ESR, High ripple current
- Inverter smoothing, Snubber circuit
- Various terminal shapes

◆SPECIFICATIONS EXAMPLE

Category Temperature Range	-40°C~+85°C
Rated Voltage Range(UR)	MPC: 600~1600VDC, MPCA: 200~500VAC
Rated Capacitance Range	0.47~100μF


MPV/MPVA SERIES
◆FEATURES•APPLICATION

- Low ESR, High ripple current
- Inverter smoothing capacitors for Industrial
- Various terminal shapes

◆SPECIFICATIONS EXAMPLE

Category Temperature Range	-40°C~+85°C
Rated Voltage Range(UR)	MPV: 250~1200VDC, MPVA: 250~800VAC
Rated Capacitance Range	47~1000μF


HVC SERIES
◆FEATURES•APPLICATION

- Inverter smoothing capacitor's unit for HEV/EV
- Miniaturized, Low ESR, Low ESL
- Custom design available

◆SPECIFICATIONS EXAMPLE

Category Temperature Range	-40°C~+85°C
Rated Voltage Range(UR)	250~2000VDC
Rated Capacitance Range	100~2200μF


PCK SERIES
◆FEATURES•APPLICATION

- High ripple current, Low buzz
- Resonance circuit, Inverter smoothing, Snubber circuit

◆SPECIFICATIONS EXAMPLE

Category Temperature Range	-40°C~+105°C
Rated Voltage Range(UR)	250~4000VDC
Rated Capacitance Range	0.027~39μF

