



RELIABILITY TEST DATA




TEST ITEM : 1) Load Life Test
 2) Shelf Life Test
 3) CHARACTERISTICS VS. TEMPERATURE

PRODUCTS : 400 EXW 15 M EFR 10X20
 450 EXW 120 M EFR 18X50
 500 EXW 27 M EFC 18X20

THE TEST RESULT

RUBYCON CORPORATION



PROJECT: Load Life Test	
SAMPLE: 400 EXW 15 M EFR 10X20	SIZE: Dia. 10 × 20 L
TESTING METHODS: The capacitor under test shall be applied the rated voltage continuously at 125°C.	APPARATUS: YHP MODEL 4274A LCR METER (at 120Hz)
NOTE: n = 10	



THE TEST RESULT

RUBYCON CORPORATION

PROJECT: Shelf Life Test	
SAMPLE: 400 EXW 15 M EFR 10X20	SIZE: Dia. 10 × 20 L
TESTING METHODS: Capacitors shall be stored at 125 ±2°C without loading for 500 Hrs.	APPARATUS: YHP MODEL 4274A LCR METER (at 120Hz)
NOTE: n = 10	



CHARACTERISTICS VS. TEMPERATURE



RUBYCON CORPORATION

SAMPLE :

400 EXW 15 M EFR 10X20

n=3




Apparatus :
Agilent Technologies - E4980A



THE TEST RESULT

RUBYCON CORPORATION




PROJECT: Load Life Test	
SAMPLE: 450 EXW 120 M EFR 18X50	SIZE: Dia. 18 × 50 L
TESTING METHODS: The capacitor under test shall be applied the rated voltage continuously at 125°C.	APPARATUS: YHP MODEL 4274A LCR METER (at 120Hz)
NOTE: n = 10	



THE TEST RESULT

RUBYCON CORPORATION

PROJECT: Shelf Life Test	
SAMPLE: 450 EXW 120 M EFR 18X50	SIZE: Dia. 18 × 50 L
TESTING METHODS: Capacitors shall be stored at 125 ±2°C without loading for 500 Hrs.	APPARATUS: YHP MODEL 4274A LCR METER (at 120Hz)
NOTE: n = 10	



CHARACTERISTICS VS. TEMPERATURE



RUBYCON CORPORATION

SAMPLE :

450 EXW 120 M EFR 18X50

n=3




Apparatus :
Agilent Technologies - E4980A



THE TEST RESULT

RUBYCON CORPORATION




PROJECT: Load Life Test	
SAMPLE: 500 EXW 27 M EFC 18X20	SIZE: Dia. 18 × 20 L
TESTING METHODS: The capacitor under test shall be applied the rated voltage continuously at 125°C.	APPARATUS: YHP MODEL 4274A LCR METER (at 120Hz)
NOTE: n = 10	



THE TEST RESULT

RUBYCON CORPORATION

PROJECT: Shelf Life Test	
SAMPLE: 500 EXW 27 M EFC 18X20	SIZE: Dia. 18 × 20 L
TESTING METHODS: Capacitors shall be stored at 125 ±2°C without loading for 500 Hrs.	APPARATUS: YHP MODEL 4274A LCR METER (at 120Hz)
NOTE: n = 10	



CHARACTERISTICS VS. TEMPERATURE

RUBYCON CORPORATION

SAMPLE :

500 EXW 27 M EFC 18X20

n=3

Apparatus :
Agilent Technologies - E4980A

