



RELIABILITY TEST DATA




TEST ITEM : 1) Load Life Test
 2) Shelf Life Test
 3) CHARACTERISTICS VS. TEMPERATURE

PRODUCTS : 25 TGV 100 M 8X10.5
 35 TGV 220 M 10X10.5
 35 TGV 560 M 12.5X16

THE TEST RESULT

RUBYCON CORPORATION



PROJECT: Load Life Test	
SAMPLE: 25 TGV 100 M 8X10.5	SIZE: Dia. 8 × 10.5 L
TESTING METHODS: The capacitor under test shall be applied the rated voltage continuously at 125°C.	APPARATUS: YHP MODEL 4274A LCR METER (at 120Hz)
NOTE: n = 10	



THE TEST RESULT

RUBYCON CORPORATION

PROJECT: Shelf Life Test	
SAMPLE: 25 TGV 100 M 8X10.5	SIZE: Dia. 8 × 10.5 L
TESTING METHODS: Capacitors shall be stored at 125 ±2°C without loading for 500 Hrs.	APPARATUS: YHP MODEL 4274A LCR METER (at 120Hz)
NOTE: n = 10	



CHARACTERISTICS VS. TEMPERATURE



RUBYCON CORPORATION

SAMPLE :

25 TGV 100 M 8X10.5

n=3




Apparatus :
Agilent Technologies - E4980A



THE TEST RESULT

RUBYCON CORPORATION



PROJECT: Load Life Test	
SAMPLE: 35 TGV 220 M 10X10.5	SIZE: Dia. 10 × 10.5 L
TESTING METHODS: The capacitor under test shall be applied the rated voltage continuously at 125°C.	APPARATUS: YHP MODEL 4274A LCR METER (at 120Hz)
NOTE: n = 10	



THE TEST RESULT

RUBYCON CORPORATION

PROJECT: Shelf Life Test	
SAMPLE: 35 TGV 220 M 10X10.5	SIZE: Dia. 10 × 10.5 L
TESTING METHODS: Capacitors shall be stored at 125 ±2°C without loading for 500 Hrs.	APPARATUS: YHP MODEL 4274A LCR METER (at 120Hz)
NOTE: n = 10	



CHARACTERISTICS VS. TEMPERATURE



RUBYCON CORPORATION

SAMPLE :

35 TGV 220 M 10X10.5

n=3




Apparatus :
Agilent Technologies - E4980A



THE TEST RESULT

RUBYCON CORPORATION




PROJECT: Load Life Test	
SAMPLE: 35 TGV 560 M 12.5X16	SIZE: Dia. 12.5 × 16 L
TESTING METHODS: The capacitor under test shall be applied the rated voltage continuously at 125°C.	APPARATUS: YHP MODEL 4274A LCR METER (at 120Hz)
NOTE: n = 10	



THE TEST RESULT

RUBYCON CORPORATION

PROJECT: Shelf Life Test	
SAMPLE: 35 TGV 560 M 12.5X16	SIZE: Dia. 12.5 × 16 L
TESTING METHODS: Capacitors shall be stored at 125 ±2°C without loading for 500 Hrs.	APPARATUS: YHP MODEL 4274A LCR METER (at 120Hz)
NOTE: n = 10	



CHARACTERISTICS VS. TEMPERATURE

RUBYCON CORPORATION

SAMPLE :

35 TGV 560 M 12.5X16

n=3

Apparatus :
Agilent Technologies - E4980A

