



RELIABILITY TEST DATA




TEST ITEM : 1) Load Life Test
 2) Shelf Life Test
 3) CHARACTERISTICS VS. TEMPERATURE

PRODUCTS : 16 ZLH 2700 M EFC 12.5X25
 50 ZLH 56 M EFC 6.3X11
 100 ZLH 68 M EFC 8X20

THE TEST RESULT

RUBYCON CORPORATION



PROJECT: Load Life Test	
SAMPLE: 16 ZLH 2700 M EFC 12.5X25	SIZE: Dia. 12.5 × 25 L
TESTING METHODS: The capacitor under test shall be applied the rated voltage continuously at 105°C.	APPARATUS: YHP MODEL 4274A LCR METER (at 120Hz)
NOTE: n = 10	



THE TEST RESULT

RUBYCON CORPORATION

PROJECT: Shelf Life Test	
SAMPLE: 16 ZLH 2700 M EFC 12.5X25	SIZE: Dia. 12.5 × 25 L
TESTING METHODS: Capacitors shall be stored at 105 ±2°C without loading for 1000 Hrs.	APPARATUS: YHP MODEL 4274A LCR METER (at 120Hz)
NOTE: n = 10	



CHARACTERISTICS VS. TEMPERATURE



RUBYCON CORPORATION

SAMPLE :

16 ZLH 2700 M EFC 12.5X25

n=3




Apparatus :
Agilent Technologies - E4980A



THE TEST RESULT

RUBYCON CORPORATION




PROJECT: Load Life Test	
SAMPLE: 50 ZLH 56 M EFC 6.3X11	SIZE: Dia. 6.3 × 11 L
TESTING METHODS: The capacitor under test shall be applied the rated voltage continuously at 105°C.	APPARATUS: YHP MODEL 4274A LCR METER (at 120Hz)
NOTE: n = 10	



THE TEST RESULT

RUBYCON CORPORATION

PROJECT: Shelf Life Test	
SAMPLE: 50 ZLH 56 M EFC 6.3X11	SIZE: Dia. 6.3 × 11 L
TESTING METHODS: Capacitors shall be stored at 105 ±2°C without loading for 1000 Hrs.	APPARATUS: YHP MODEL 4274A LCR METER (at 120Hz)
NOTE: n = 10	



CHARACTERISTICS VS. TEMPERATURE



RUBYCON CORPORATION

SAMPLE :

50 ZLH 56 M EFC 6.3X11

n=3




Apparatus :
Agilent Technologies - E4980A



THE TEST RESULT

RUBYCON CORPORATION




PROJECT: Load Life Test	
SAMPLE: 100 ZLH 68 M EFC 8X20	SIZE: Dia. 8 × 20 L
TESTING METHODS: The capacitor under test shall be applied the rated voltage continuously at 105°C.	APPARATUS: YHP MODEL 4274A LCR METER (at 120Hz)
NOTE: n = 10	



THE TEST RESULT

RUBYCON CORPORATION

PROJECT: Shelf Life Test	
SAMPLE: 100 ZLH 68 M EFC 8X20	SIZE: Dia. 8 × 20 L
TESTING METHODS: Capacitors shall be stored at 105 ±2°C without loading for 1000 Hrs.	APPARATUS: YHP MODEL 4274A LCR METER (at 120Hz)
NOTE: n = 10	



CHARACTERISTICS VS. TEMPERATURE

RUBYCON CORPORATION

SAMPLE :

100 ZLH 68 M EFC 8X20

n=3

Apparatus :
Agilent Technologies - E4980A

